



601 Natural/Tint Base
602 Golden Oak
603 Cherry
604 Red Mahogany

PRODUCT NUMBER

605 Provincial
606 Maple
607 Early American
608 Dark Mahogany
609 Cedar
610 Dark Walnut
611 Special Walnut
612 Spanish Oak
613 Fruitwood
614 Pickling White
615 Puritan Pine

PRODUCT DESCRIPTION

Old Masters® Fast Dry Wood Stain is designed for the professional craftsman. This high quality oil-based stain applies easily and enhances the wood's natural grain with its intensified depth of color and clarity. Its rapid dry time and superior performance allow every project to be topcoated more quickly, granting a more efficient turnaround. The low-solvent odor makes this a great alternative to lacquer stains. Experience optimal results on all interior wood surfaces such as cabinets, doors, floors, furniture and woodwork.

Available in quart (04), gallon (01), and 5's(05)

PHYSICAL PROPERTIES

Gloss	Not applicable
Solids By Weight	35.7% to 44.9%
Solids By Volume	29.4% to 29.6%
V.O.C.	550 grams/liter
Theoretical Coverage @ 1 Mil DFT	Not Applicable
Coverage @ Recommended DFT	Not Applicable
Recommended DFT Per Coat	Not Applicable
Weight Per Gallon	7.1 to 8.3 lbs
Flash Point	102°F TAG Closed Cup
Viscosity @ 77°F	15 sec. Ford Cup #2
Average Dry Time @ 70°F & 50% R.H.	30 to 60 minutes
Vehicle	Alkyd
Solvent System	Mineral Spirits
Recommended Thinner	Do not thin. Use as packaged.

MIXING SPECIAL COLORS

Special colors may be created in several ways: by intermixing any Fast Dry Wood Stain colors, existing colors may be modified and new colors may be created. Custom colors may be achieved by adding up to 14 ounces of universal or industrial colorant per gallon to any Fast Dry Wood Stain or by adding colorant to Natural/Tint Base Fast Dry Wood Stain. Natural/Tint Base Fast Dry Wood Stain may be used to lighten a Fast Dry Wood Stain color in any proportion, or as a tint base to which colorant may be added for ultimate color selection. Create Santa Fe pastel colors by tinting Pickling White Fast Dry Wood Stain with universal colorant (formulas available upon request). The amount of colorant added may affect its performance and extend the dry time.

HELPFUL HINTS

Color depth may vary according to wood type and application method used. Before staining, test stain in an inconspicuous area. For a deeper color – allow the surface to dry, then apply a second coat. For a lighter color – before the stain has dried, wipe the surface with a cloth dampened with mineral spirits.

Fast Dry Wood Stain

PRODUCT DATA SHEET

SURFACE PREPARATION

The wood surface must be clean, dry and free from dirt, wax, or grease. Sand the wood thoroughly, first with medium grit sandpaper, then progressing to a fine grit paper. Always sand in the direction of the wood grain. Sand smooth, then remove dust particles with a lint-free rag or a tack rag. If staining previously finished surfaces, first restore the surface to bare wood by completely removing the old finish, then follow the surface preparation directions listed above.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

APPLICATION

Stir well before and during use. For projects requiring more than one container of the same color, stir well, and then intermix to avoid any color difference. Apply an even coat of Fast Dry Wood Stain with a brush, cloth, pad, roller, or sprayer. Allow the stain to penetrate 2 to 5 minutes. Before the stain dries, wipe off excess stain with a soft cloth – wiping first across the grain, then with the grain. Allow stain to dry thoroughly before applying top coating. For added protection, top coat with any Old Masters® clear finish.

RECOMMENDED FINISH COAT

We recommend Old Masters® clear finishes. However, Fast Dry Wood Stain projects can be top coated with virtually any finish including professional finishes such as lacquers and conversion varnishes. When applying waterborne finishes, be sure stain is solvent-free before topcoating or consult manufacturer's label for recommendations.

COVERAGE

Approximately 500 square feet per gallon depending on the porosity and texture of the wood.

DRYING TIME

Finish may be applied 30 minutes after wiping. Dry times may be extended due to humidity, low temperature, lack of air movement, excess stain application or lack of penetration. Be sure surface is thoroughly dry before topcoating.

Ideal drying conditions recommended are 70° to 75°F and 35 to 50% humidity.

CLEAN UP

Clean up with mineral spirits or a paint thinner. To avoid spontaneous combustion during temporary storage, soak soiled rags and waste immediately after use in a water-filled, closed metal container.

For additional technical information, please see your specialized Old Masters® dealer or contact Old Masters® at 800-747-3436 and request technical service.

LIMITED WARRANTY: Since Old Masters® does not control the application of its products, nor the condition of the surfaces to which they are applied, a Limited Warranty is provided. If the products do not perform as specified, for whatever reason, Old Masters® liability will under no circumstances exceed replacement of the product.



303 19th St. SE · Orange City, IA 51041
Ph. 800-747-3436 · Fax 712-737-3436

www.oldmasters.biz