



1900 Albany Place SE  
 P.O. Box 286  
 Orange City, IA 51041

800-737-3436 Fax 712-737-3893  
 www.oldmastrs.com

## PRODUCT INFORMATION

### *SPAR-MARINE VARNISH SATIN*

<b>PRODUCT NO.</b>	92301, 92304, 92305, 92308, 92310
<b>GENERIC TYPE</b>	Tung-Phenolic Varnish
<b>COLOR</b>	Clear
<b>GLOSS</b>	25 to 30 @ 60°
<b>SOLIDS BY WEIGHT</b>	52%
<b>SOLIDS BY VOLUME</b>	42.4%
<b>VOC</b>	450 grams/liter
<b>THEORETICAL COVERAGE @ 1 MIL DFT</b>	680 sq. ft. per gallon
<b>COVERAGE @ RECOMMENDED DFT</b>	250 to 350 sq. ft. per gallon
<b>RECOMMENDED DFT PER COAT</b>	2 to 3 mils
<b>WEIGHT PER GALLON</b>	7.8 lbs.
<b>FLASH POINT</b>	102°F Tag Closed Cup
<b>USE</b>	Recommended for interior and exterior surfaces which are exposed to severe wear or weather.
<b>VISCOSITY AT 77°F</b>	25 to 30 sec. #4 Ford Cup
<b>AVERAGE DRY TIME AT 70°F &amp; 50% R.H.</b>	4 to 6 hours dry to touch, recoat after 8 to 16 hours
<b>RECOMMENDED THINNER</b>	Do not thin.
<b>APPLICATION</b>	Apply with a brush, roller, sprayer or flat applicator. If brushing, use a pure bristle or ox hair brush.
<b>SURFACE PREPARATION</b>	Sand and remove dust.
<b>CLEAN-UP</b>	Mineral Spirits

**FOR THE LOVE OF WOOD®**

Interior Wood Stains, Clears, Removers & Miscellaneous Sundries



## PRODUCT INFORMATION

### **SPAR-MARINE VARNISH SATIN**

**DESCRIPTION:** OLD MASTERS® SPAR-MARINE VARNISH, a superior exterior coating formulated with Tung Oil and Ultraviolet Absorbers (UVA), produces a high quality, flexible finish that withstands weathering due to sun, water and salt spray. SPAR-MARINE VARNISH provides an extremely durable coating for all exterior wood surfaces, such as fences, railings, lawn furniture, doors, boats and marine surfaces. SPAR-MARINE VARNISH may be used in interior applications where added protection is necessary, such as interior window sills. SPAR-MARINE VARNISH requires no sealer on new wood and may be applied over previously varnished, lacquered or stained surfaces which are free of waxes, silicones, household greases or other substances which would impair adhesion.

**THINNING:** Do not thin. Use as packaged.

**SURFACE PREPARATION:** The wood surface must be clean, dry and free from dirt, wax or grease. For NEW WOOD SURFACES, eliminate imperfections by first sanding the surface with a fine grit sandpaper, then removing dust with a tack rag. For STAINED SURFACES, apply stain and allow to dry thoroughly prior to applying SPAR-MARINE VARNISH. If a sealer is desired, we recommend Old Masters® Penetrating Sealer. On PREVIOUSLY FINISHED SURFACES, clean the surfaces with mineral spirits, then sand well in order to remove imperfections, smooth the surface and de-gloss the finish. Remove sanding dust with a tack rag.

**APPLICATION:** DO NOT SHAKE. Stir satin and semi-gloss finishes thoroughly before and during application. Apply SPAR-MARINE VARNISH with pure bristle or polyester brush, flat pad or spray. Flow on with minimum brushing to achieve a glass-like finish. Allow each coat to dry 8 to 16 hours prior to recoating. Always sand lightly between coats to produce a finer finish and to promote adhesion. For exterior surfaces, a minimum of three coats should be applied.

**IMPORTANT:** DO NOT varnish before morning dew has evaporated or 2 hours before sunset. Avoid varnishing on damp, humid days. Keep work area as dust free as possible until SPAR-MARINE VARNISH has thoroughly dried. A slight ambering effect may occur over light colored surfaces.

**SPREADING RATE:** Approximately 500 square feet per gallon on the first coat. On subsequent coats, the rate will be 500 to 700 square feet per gallon.

**DRYING TIME:** SPAR-MARINE VARNISH dries to touch in 4 to 6 hours. Under good conditions the surface may be recoated in 8 to 16 hours. High humidity, low temperature or lack of air movement will extend drying time.

**CLEAN-UP:** Clean up with mineral spirits.  
MAX. VOC: 450 grams/liter (3.75 lbs/gal)

### **WARNING! COMBUSTIBLE LIQUID AND VAPOR.**

**Contains: Petroleum Distillate.** VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAUSES NOSE, THROAT, EYE AND SKIN IRRITATION. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Keep away from heat and flame. **Use only with adequate ventilation.** Close container after each use. Avoid prolonged contact with eyes, skin, clothing and vapors. Wash thoroughly after handling. **KEEP OUT OF REACH OF CHILDREN. First Aid:** In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. If swallowed, do not induce vomiting. Call physician immediately. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.regulations.

---

### **Limited Warranty**

Since Old Masters® does not control the application of its products, nor the condition of the surfaces to which they are applied, a Limited Warranty is provided. If the products do not perform as specified, for whatever reason, Old Masters® liability will under no circumstances exceed replacement of the product.

---

OLD MASTERS®  
1900 ALBANY PLACE SE  
ORANGE CITY, IA 51041