



1900 Albany Place SE
P.O. Box 286
Orange City, IA 51041

800-747-3436 Fax 712-737-3893
www.oldmastrs.com

PRODUCT INFORMATION

SPAR-MARINE VARNISH SEMI-GLOSS

PRODUCT NO.	92501, 92504, 92505, 92508
GENERIC TYPE	Linseed Tung-Phenolic Varnish
COLOR	Clear
GLOSS	45 to 50 @ 60°
SOLIDS BY WEIGHT	49.8%
SOLIDS BY VOLUME	41.6%
V.O.C.	450 grams/liter
THEORETICAL COVERAGE @ 1 MIL DFT	667 sq. ft. per gal.
COVERAGE @ RECOMMENDED DFT	200 to 325 sq. ft. per gal.
RECOMMENDED DFT PER COAT	2 to 3 Mils
WEIGHT PER GALLON	7.5 lbs.
FLASH POINT	102°F Tag Closed Cup
USE	Recommended for interior and exterior surfaces which are exposed to severe wear or weather.
VISCOSITY AT 77°F	35 to 45 sec. #4 Ford Cup
AVERAGE DRY TIME AT 70°F & 50% R.H.	4 to 6 hours dry to touch, recoat after 8 to 16 hours
RECOMMENDED THINNER	Do not thin.
APPLICATION	Apply with a brush, roller, sprayer or flat applicator. If brushing, use a pure bristle or ox hair brush.
SURFACE PREPARATION	Sand and remove dust.
CLEAN UP	Mineral Spirits

FOR THE LOVE OF WOOD®

Interior Wood Stains, Clears, Removers & Miscellaneous Sundries



PRODUCT INFORMATION

SPAR-MARINE VARNISH SEMI-GLOSS

DESCRIPTION: OLD MASTERS® SPAR-MARINE VARNISH, a superior exterior coating formulated with Tung Oil and Ultraviolet Absorbers (UVA), produces a high quality, flexible finish that withstands weathering due to sun, water, and salt spray. SPAR-MARINE VARNISH provides an extremely durable coating for all exterior wood surfaces, such as fences, railings, lawn furniture, doors, boats, and marine surfaces. SPAR-MARINE VARNISH may be used in interior applications where added protection is necessary, such as interior window sills. SPAR-MARINE VARNISH requires no sealer on new wood and may be applied over previously varnished, lacquered, or stained surfaces which are free of waxes, silicones, household greases, or other substances which would impair adhesion.

THINNING: Do not thin. Use as packaged.

SURFACE PREPARATION: The wood surface must be clean, dry, and free from dirt, wax, or grease. For NEW WOOD surfaces, eliminate imperfections by first sanding the surface with a fine grit sandpaper, then removing dust with a tack rag. For STAINED SURFACES, apply stain and allow to dry thoroughly prior to applying SPAR-MARINE VARNISH. If a sealer is desired, we recommend OLD MASTERS® PENETRATING SEALER. On PREVIOUSLY FINISHED SURFACES, clean the surfaces with mineral spirits, then sand well in order to remove imperfections, smooth the surface, and de-gloss the finish. Remove sanding dust with a tack rag.

APPLICATION: DO NOT SHAKE. Stir semi-gloss finish thoroughly before and during application. Apply SPAR-MARINE VARNISH with pure bristle or polyester brush, flat pad, or spray. Flow on with minimum brushing to achieve a glass-like finish. Allow each coat to dry 8 to 16 hours prior to recoating. Always sand lightly between coats to produce a finer finish and to promote adhesion. For exterior surfaces, a minimum of three coats should be applied.

IMPORTANT: DO NOT varnish before morning dew has evaporated or two hours before sunset. Avoid varnishing on damp, humid days. Keep work area as dust free as possible until SPAR-MARINE VARNISH has thoroughly dried. A slight ambering effect may occur over light colored surfaces.

SPREADING RATE: Approximately 500 square feet per gallon on the first coat. On subsequent coats, the rate will be 500 to 700 square feet per gallon.

DRYING TIME: SPAR-MARINE VARNISH dries to touch in 4 to 6 hours. Under good conditions the surface may be recoated in 8 to 16 hours. High humidity, low temperature, or lack of air movement will extend drying time.

CLEAN UP: Clean up with mineral spirits.

MAX. VOC: 450 grams/liter (3.75 lbs/gal)

WARNING! COMBUSTIBLE LIQUID AND VAPOR.

CONTAINS PETROLEUM DISTILLATE. VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE, OR NAUSEA. CAUSES NOSE, THROAT, EYE, AND SKIN IRRITATION. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Keep away from heat and flame. **Use only with adequate ventilation.** Close container after each use. Avoid prolonged contact with eyes, skin, clothing, and vapors. Wash thoroughly after handling. **KEEP OUT OF REACH OF CHILDREN. FIRST AID:** In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. If swallowed, do not induce vomiting. Call physician immediately. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

Limited Warranty

Since Old Masters® does not control the application of its products, nor the condition of the surfaces to which they are applied, a Limited Warranty is provided. If the products do not perform as specified, for whatever reason, Old Masters® liability will under no circumstances exceed replacement of the product.

OLD MASTERS®
1900 ALBANY PLACE SE
ORANGE CITY, IA 51041